

OPC-12/24/36/48/72/96/144 Ports ODF

Features:

Standard size, can be rackmount and wallmount
 Splice tray inside changeable
 Can be used in 19", 23" standard distribution frame
 Suitable for ribbon and single fiber
 Various panel plate to fit different adapter interface
 Front mark on the plate is easy for identification and operation
 24C, 36C, 48C, 72C, 96C, 144C optional
 with or without fiber optic pigtailed and adapters.



Application:

Telecommunications subscriber loop
 Fiber to the home (FTTH)
 LAN/WAN
 CATV

Specification:

Model	Core Count	Height	Dimension(cm)	Weight(kg)
OPC-ODF-144	144	7U	49x30.5x31.15 or customer request	17.1
OPC-ODF-96	96	5U	49x30.5x22.25 or customer request	11
OPC-ODF-72	72	4U	49x30.5x17.8	9
OPC-ODF-48	48	3U	49x30.5x13.35	7
OPC-ODF-36	36	2U	49x30.5x8.9	5.7
OPC-ODF-24	24	2U	49x30.5x8.9	4.6



Order Information:

OPC-ODF-①②③④⑤⑥⑦

①Port Number

1=12 cores
 2=24 cores
 3=36 cores
 4=48 cores
 5=72 cores
 6=96 cores
 7=144 cores

②Adapter

0=Without Adapter
 1=FC
 2=SC(Simplex or Duplex)

 C=Customized

③Pigtail

0=Without pigtail
 1=SM-SX-SC/PC-1.5m

 C=Customized