

OPC-Adaptor Series

Features:

- Low insertion loss, high return loss
- High credibility and stability
- Ceramic or Bronze Sleeve
- Good in repeatability and exchangeability
- PC、APC、UPC optional Simplex or Duplex

Application:

- Local Area Network
- CATV System
- Telecommunication Networks
- Equipment Test



Specification:

Parameter	Unit	LC, SC, FC, MU, ST, SC-ST, FC-ST, FC-SC, FC-LC, FC-MU				MTRJ			E2000		
		SM		MM		SM		MM		SM	
		PC	UPC	APC	PC	PC	UPC	PC	PC	APC	
Insertion Loss (Typical)	dB	≤0.3	≤0.2	≤0.3	≤0.2	≤0.3	≤0.2	≤0.2	≤0.3	≤0.3	
Return Loss	dB	≥45	≥50	≥60	≥30	≥45	≥50	≥35	≥55	≥75	
Exchangeability	dB	≤0.2				≤0.2			≤0.2		
Repeatability	dB	≤0.2				≤0.2			≤0.2		
Durability	Time	>1000				>1000			>1000		
Operating Temperature	°C	-40~75				-40~75			-40~75		
Storage Temperature	°C	-45~85				-45~85			-45~85		



Order Information:

ADAP-①-②-③-④

①Configuration

Simplex
Duplex
Quad(LC only)

②Housing Material

Metal
Plastic

③Style

D-type(FC only)
Flange
No Flange
Round
Square(FC only)
Rectangle(ST Duplex)

④Adapter Type

FC
SC
LC
ST
MU
FC-SC
FC-ST
SC-ST
E2000
MTRJ
MPO